



TECHSPRAY®


www.techspray.com

MAINTENANCE & REPAIR


PRECISION CLEANING

PCB ASSEMBLY

REWORK & REPAIR



PRODUCT CATALOG & APPLICATION GUIDE





Dusters

Techspray dusters blow away dust, microscopic contaminants, lint, metallic oxide deposits and other soils that can cause heat build-up or shorts in sensitive electronics. They are completely portable, ultra-pure, and free of moisture, oil, and other contaminants.

- Moisture free
- Non-ozone depleting
- Zero residue
- VOC exempt
- Safe on plastics

Nonflammable Duster

Nonflammable, 100% HFC-134a duster

1671-10S 10 oz. (283g) aerosol

1671-15S 15 oz. (425g) aerosol

CAN1671-10S 10 oz. (283g) aerosol

Canada compliant packaging

CAN1671-15S 15 oz. (425g) aerosol

Canada compliant packaging



1671-10S 1671-15S



Vortex™ High Velocity Duster

High velocity, 100% HFC-134a duster

- Most powerful blast
- Nonflammable
- Safest choice for energized equipment
- Vortex 360° sprays upside-down
- Velocity – 14.6 m/s

1697-8S Vortex 360° 8 oz. (227g) aerosol

1697-10S 10 oz. (283g) aerosol



1697-8S 1697-10S

Economy Duster

Economical HFC-152a duster

- Best value – 30% more volume
- Lower global warming potential – 10% of HFC-134a
- Velocity – 11.4 m/s

1673-10S 10 oz. (283g) aerosol

Note: not for use on powered electrical equipment, on hot surfaces, and around open flames or sparks.



1673-10S



Renew-Duster

1580-10S 10 oz. (283g) aerosol



- GWP less than 1/100th of HFC-134a
- Nonflammable
- Non-ozone depleting
- Velocity – 12 m/s

DUSTER SELECTION GUIDE

	Spray Power	Nonflammable	360° Spray	Contents	GWP*	Use On Live Circuits
1697-10S Vortex Duster	Best	Yes	No	HFC-134a	1300	Yes
1697-8S Vortex 360° Duster	Best	Yes	Yes	HFC-134a	1300	Yes
1671 Duster	Good	Yes	No	HFC-134a	1300	Yes
1673 Economy Duster	Good	No	No	HFC-152a	140	No
1580 Renew-Duster	Good	Yes	No	HFO-1234ze	6	Yes

* Global warming potential (GWP) is calculated based on a 100 year time horizon. Carbon dioxide has a GWP of 1.

Isopropyl Alcohol (IPA)

Techspray has the broadest line of isopropyl alcohol (IPA) in the industry, ranging from aerosol, pre-saturated wipes, and bulk packaging. Two grades of IPA are available: 99.8% anhydrous (containing as little water as possible) for fast-drying cleaning and 70% IPA / 30% DI for stencil and other cleaning when slower evaporation is desired.

70% Bulk – Cleaning Grade IPA

1608-G4 1 gal. (3.8L) container

99.8% Bulk – Technical Grade IPA

1610-P 1 pt. (473mL) bottle

1610-PT 1 pt. (473mL) bottle
w/ trigger sprayer

1610-G1 1 gal. (3.8L) bottle

1610-G4 1 gal. (3.8L) bottle sold only 4/cs

1610-5G 5 gal. (19L) container

1610-54G 54 gal. (205L) drum

Specs: 99.8% IPA filtered to 0.2 microns, fed spec TT-1-735A (amend 3, notice 2) grades A&B, ASTM D770-05



Pop-up Tub

- 5"x8" (127mm x 203mm) wipes
- 100 wipes/tub
- Lint-free, tear resistant polyester

70% IPA Wipes

- 1608-100DSP** 100 wipes in Disposable Tub
1608-100FL 100 wipes in Flip-Top Tub
1608-100R 100 wipes refill roll

99.8% IPA Wipes

- 1610-100DSP** 100 wipes in Disposable Tub
1610-100FL 100 wipes in Flip-Top Tub
1610-100R 100 wipes refill roll



Individually Wrapped Wipes

- 99.8% pure IPA
- 5.5"x5.5" (140mm x 140mm) wipes
- 50 wipes/box
- Lint-free, tear resistant poly-cellulose

1610-50PK



E-Line IPA Electronics Cleaner

99.8% IPA in convenient aerosol package

- 99.8% pure IPA
- Compliant with SCAQMD rule 1171
- Plastic safe
- Low toxicity
- Non-ozone depleting
- NSF registered K1, K2

1610-12S 12 oz. (340g) aerosol

Specifications for 99.8% IPA: Fed spec TT-1-735A (amend 3, notice 2) grades A&B, ASTM D770-05



Precision, Safety, Performance . . . Advanced Chemistries to Improve Your Products & Processes.

Techspray® offers cutting-edge technologies to improve your processes. Several formulas are available for applications ranging from electronics cleaning to heavy-duty industrial cleaning.



POWERFUL, NONFLAMMABLE & COST EFFECTIVE CLEANER

- Ideal replacement for n-propyl bromide (nPb) and other toxic industrial solvents
- Available in aerosol or bulk for vapor degreasing, ultrasonic and soak applications
- PWR-4™ Maintenance Cleaner for heavy-duty degreasing and contact cleaning, PWR-4™ Flux Remover for PCB cleaning



NONFLAMMABLE & POWERFUL CLEANER

- Top-selling solvent that's effective on the broadest array of soils
- Available in aerosol or bulk for ultrasonic and soak applications



NONFLAMMABLE, POWERFUL & HIGH PRECISION CLEANER

- Replacement for AK225, which was banned because of environmental issues
- Ideal for aviation, aerospace, medical and military applications
- Available in aerosol or bulk for vapor degreasing, ultrasonic and soak applications



ECONOMICAL & POWERFUL CLEANER, BUT FLAMMABLE

- Effective cleaner and safe on sensitive plastics
- Available in aerosol or bulk for ultrasonic and soak applications



HIGH PERFORMANCE ECO-FRIENDLY CLEANERS

- Water-based flux removers with zero GWP and low VOC
- Engineered for batch and inline equipment



SAFER REPLACEMENTS FOR TOXIC INDUSTRIAL SOLVENTS

n-Propyl Bromide (nPb), Trichloroethylene (TCE), and Perchloroethylene (Perc) are three examples of harmful chemicals that are commonly used in aerosol cleaners for industrial applications. These chemicals have been popular because they are nonflammable, have high solvency, and are relatively inexpensive.

Because of safety concerns, these solvents are under close scrutiny by OSHA, EPA, and local agencies. For example, The American Conference of Governmental Industrial Hygienists (ACGIH) recommends a 10 ppm time-weighted average threshold limit of nPB, but has proposed a lower 0.1 ppm (ACGIH 2013). That's because nPB is a suspected human carcinogen, and has shown to negatively impact neurological and reproductive functioning.

Techspray offers effective replacements for these toxic solvents. PWR-4® High Performance Solvents provides all the cleaning power of nPB and other industrial solvents, but without the health risks.

For more information, read "Toxic Chemicals Used for Industrial Cleaning" white paper at www.techspray.com





TECHSPRAY®

Degreasers / Contact Cleaners



Maintenance Cleaner

Blasts away oil and contaminants off of contacts, printed circuit boards, barcode instruments, switch boxes, gear boxes, and electronic motor controllers. Grease and oil flow right off, reducing the time and materials needed to scrub off stubborn soils.

- Nonflammable
- Much safer than most common industrial solvents — TCE, nPB, Perc & Methylene Chloride
- Powerful cleaner — Ideal for degreasing and contact cleaning
- Available in aerosol or bulk for vapor degreasing, ultrasonic and immersion cleaning
- Rapid evaporation
- Non-ozone depleting
- Cleaning applications: electronics, relays, switches & breakers, transformers, and electric motors and generators
- NSF registered K1, K2



3400-20S 20 oz. (567g) aerosol
3400-G 1 gal. (3.8L) pail
3400-5G 5 gal. (18.9L) pail
3400-54G 54 gal. (204L) drum



MAINTENANCE CLEANER SELECTION GUIDE

Maintenance cleaners clean oil and contaminants off of metal parts, printed circuit boards, barcode instruments, switch boxes, gear boxes, and engines.



PROPERTIES												
Nonflammable	●	●	●		●	●	●	●	●			
Sensitive plastics					●			●	●	●	●	●
Evaporation rate (1=slow, 5=fast)	5	5	5	4	5	5	5	5	3	4	4	4
VOC% (EPA) - Aerosol	70	64	64	69	-	37	65	12.6	75	75	75	-
VOC% (EPA) - Bulk	95	-	-	-	61	49	-	-	100	-	-	100
VOC% (CARB) - Aerosol	73	75	75	69	-	75	-	-	75	75	75	-
VOC% (CARB) - Bulk	100	-	-	-	100	100	-	-	100	-	-	100
Dielectric Strength (kV)	24 kV	27 kV	36 kV	-	27 kV	14 kV	14 kV	12 kV	-	-	-	-
kB Values	100	83	78	89	78	54	79	29	-	87	87	87
APPLICATIONS												
Benchtop cleaning	●	●	●	●	●	●	●	●	●	●	●	●
Ultrasonic	●				●	●		*			*	
Vapor degreasing	●											

NOTE: Test for substrate compatibility as a part of your qualification process.

* Non-heated ultrasonic only

MAINTENANCE & REPAIR



Blue Shower Maintenance Cleaner

Nonflammable, powerful cleaner

Clean oil and contaminants off of metal parts, printed circuit boards, barcode instruments, switch boxes, gear relays, and electronic motor controllers.

1630-16S 16 oz. (454g) aerosol



- Nonflammable
- Powerful cleaner
- Rapid evaporation
- Non-ozone depleting
- Dielectric strength – 27.3 kV
- NSF registered K1, K2

Compliant with Boeing D6 17487, Rev T



Industrial Maintenance Cleaner

High power, fast evaporating maintenance cleaner

Blast away heavy oils and greases off of metal parts, gear boxes, and engines.

1635-20S 20 oz. (567g) aerosol



- All-in-one electronic maintenance & contact cleaner
- Rapid evaporation
- Non-ozone depleting
- Low toxicity compared to TCE, nPB & Perc
- Dielectric strength – 30.5 kV



Universal Cleaner

Nonflammable, powerful liquid cleaner

Engineered to remove oils, fluxes and other contamination using a manual soak cleaning process or ultrasonic equipment.

1638-G 1 gal. (3.8L) pail

1638-5G 5 gal. (19L) pail

1638-54G 54 gal. (205L) drum



- Nonflammable
- Powerful cleaner
- Effective as maintenance cleaner and flux remover
- Rapid evaporation
- Non-ozone depleting
- Dielectric strength – 27.3 kV



Contact Cleaner

Nonflammable, powerful contact cleaner

Clean oxidation, oil, and other contaminants from contacts, metal switches, relays, edge connectors, buss bars, and circuit breakers.

1632-16S 16 oz. (454g) aerosol



- Nonflammable
- Powerful cleaner
- Rapid evaporation
- Non-ozone depleting
- Dielectric strength – 36.2 kV
- NSF registered K1, K2

Compliant with Boeing D6 17487, Rev T



Flux Remover & Maintenance Cleaner

Nonflammable and powerful precision cleaner

Clean off flux residues, oil, and other contamination from electronics and other sensitive surfaces.

1651-16S 16 oz. (454g) aerosol

1651-5G 5 gal. (19L) pail

1651-54G 54 gal. (205L) drum



- Nonflammable
- Low VOC
- Safe on most plastics
- High precision – residue-free
- Rapid evaporation
- Non-ozone depleting
- Dielectric strength – 14 kV



TECHSPRAY®

Specialized Degreasers for Aviation and Aircraft Parts

These specially engineered aviation degreasers quickly remove hydraulic fluid, fuel oils, lubricating oils and greases, and other organic residues. They are fast evaporating, quick penetrating, and ideal for cleaning aviation parts. Both are free of hazardous air pollutants (HAPs), and CARB compliant.



Aviation Degreaser

Exceptional nonflammable cleaner for aircraft parts degreasing

Specially engineered aviation degreaser featuring powerful removal of hydraulic fluid, fuel oils, lubricating oils and greases, and other organic residues. PWR-4 Aviation Degreaser features a powerful, long reaching spray to clean hard-to-reach parts from as far as 10 feet.

2851-20S 20 oz (567g) aerosol

Specifications: Meets Airbus UK ABR9-0140 General Purpose Cleaning Solvent, FedEx CPN 0311737, Boeing D6 17487, Rev T



- Nonflammable
- Fast evaporation
- Zero residue
- Non-ozone depleting
- Does not contain n-propyl bromide
- Dielectric breakdown of 13.7 kV
- CARB compliant

Aviation Degreaser II

NESHAP compliant cleaner for removing hydraulic and lubricating fluids

1647-16S 16 oz. (454g) aerosol

Specifications: Meets Boeing D6 17487, Rev T, NESHAP 63.741-753



- Nonflammable
- Low VOC / NESHAP compliant
- Fast evaporation
- Zero residue
- Non-ozone depleting
- Does not contain n-propyl bromide
- Dielectric breakdown of 11.9 kV
- CARB compliant

More Choices for Aviation Cleaning:

Compliant with Boeing D6 17487, Rev T:

G3 Blue Shower Maintenance Cleaner (1630-16S)

G3 Blue Shower Contact Cleaner (1632-16S)



Blue Shower Maintenance Cleaner

Powerful and economical aerosol cleaner

Clean oil and contaminants off of metal parts, printed circuit boards, barcode instruments, switch boxes, gear boxes, and engines.

1620-10S 10 oz. (284g) aerosol



- Powerful cleaner
- Ideal for sensitive plastics
- Low toxicity
- Non-ozone depleting
- NSF registered K1, K2



Flux Remover & Maintenance Cleaner

Powerful and economical liquid cleaner

Engineered to remove oils, fluxes and other contamination using soak cleaning process or ultrasonic equipment.

1621-G 1 gal. (3.8L) pail

1621-5G 5 gal (18.9L) pail

1621-54G 54 gal. (204L) drum



- Effective as maintenance cleaner and flux remover
- Ideal for sensitive plastics
- For cold cleaning and ultrasonic (unheated only)
- Non-ozone depleting



Contact Cleaner

Powerful and economical electronic contact cleaner

Clean oxidation, oil, and other contaminants from contacts, metal switches, relays, edge connectors, buss bars, and circuit breakers.

1622-10S 10 oz. (284g) aerosol

1622-13S 13 oz. (369g) aerosol



- Powerful cleaner
- Ideal for sensitive plastics
- Low toxicity
- Non-ozone depleting



IPA Electronics Cleaner

99.8% IPA in convenient aerosol package

Ideal for defluxing, stencil cleaning and fiber optic connector cleaning.

1610-12S 12 oz. (340g) aerosol

Specifications for IPA: 99.8% IPA filtered to 0.2 microns, Fed spec TT-1-735A (amend 3, notice 2) grades A&B, ASTM D770-05



- 99.8% pure IPA
- Compliant with SCAQMD rule 1171
- Plastic safe
- Low toxicity
- Non-ozone depleting



Eco-Shine™ Glass & Surface Cleaner

Eco-friendly, nonflammable, streak-free glass cleaner

Cleans glass, stainless steel, chrome, mirrors, tile, plastic, ceramic and enamel and leaves a streak-free finish.

1505-QT 1 qt. (0.95L) w/ trigger sprayer
1505-G 1 gal. (3.8L) jug



1505-QT

- Streak-free
- Nonflammable
- Non-ammoniated – safe on sensitive surfaces
- Low VOC, no GWP
- Non-ozone depleting
- NSF registered K1, K2

Glass Cleaner

Foaming aerosol glass and surface cleaner

1625-18S 18 oz. (510g) aerosol



- Foaming action
- Streak-free
- Safe on glass & plastics
- Nonflammable

Specifications: GM H1018, Ford Tox #142432

Roller Rejuvenator & Platen Cleaner

Rubber roller cleaner and rejuvenator

Citrus-based solvent designed to clean and revitalize rubber rollers and platens. Improves rubber roller grip and reduces misfeeds and jams.

1612-2SQ 2 oz. (59ml) bottle



- Improves roller grip
- Natural citrus-based solvent
- Safe on most plastics

Specifications: Ford Tox #142415

Note: Not available in California

Label & Adhesive Remover

Fast acting, citrus-based label and adhesive remover

Citrus-based solvent safely and effectively removes labels and adhesive gums off equipment and products. Penetrates quickly and allows label to be peeled off without gummy residue.

1613-6S 4.5 oz. (128g) aerosol



- Removes labels and adhesive without scraping
- Penetrates rapidly
- Citrus-based solvent
- Safe on most plastics

Note: Not available in California

Adhesives

Low soak-in adhesive exhibits particular strength when bonding surfaces such as dry wall, brick and concrete block. Heavy Duty Adhesive will also work on surfaces such as paper, plastic, foam, wood and other fabrics. Excellent for both temporary and permanent bonds.

Heavy-Duty Adhesive

3500-11S 12 oz. (340g) aerosol



- High strength
- Fast tacking
- Water resistant
- Non-wrinking

Economy Adhesive

3505-11S 12 oz. (340g) aerosol

Contact Adhesive

3510-12S 12 oz. (340g) aerosol

3505-11S

3510-12S



TECHSPRAY®

Flux Removers

Flux removers (defluxers) remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards. Residues from higher, lead-free temperatures are more baked on and harder to clean. PWR-4™, G3®, E-LINE™ and Precision-V™ flux removers have been proven very effective at removing fluxes baked on at lead-free temperatures.

Micro-components and fine pitch leads are delicate and easily damaged, so brushing and scrubbing should be avoided if possible. Both G3, E-LINE™ and Precision-V have a powerful spray and strong solvent that blasts off residues and cleans areas under components that a brush cannot touch.

Techspray offers traditional solvent-based cleaners and cutting edge water-based technologies marketed under the Techspray Renew™ brand.



High Performance Eco-Cleaning™

TECHSPRAY RENEW™ branded cleaners are innovative solutions that combine the best of current "green" technologies to make the most powerful eco-friendly cleaners on the market.



All Techspray flux removers have the following advantages:

- Help create bright, shiny solder joints
- Improve PCB reliability
- Prevent conformal coating defects
- Prevent corrosion from contamination
- RoHS compliant

FLUX REMOVER SELECTION GUIDE

PROPERTIES	3401PWR-4 Flux Remover	1631G3 Flux Remover	1634G3 No-Clean Flux Remover	1638G3 Bulk Solvent	1651 Precision-V	1670E-LINE IPA	1621E-LINE Flux Remover	1550Eco-dFluxer SMT100	1520Eco-dFluxer SMT200	1530Eco-dFluxer SMT300
Nonflammable	●	●	●	●	●			●	●	●
Sensitive plastics				●	●	●	●	●	●	●
Evaporation rate (1=slow, 5=fast)	5	5	5	5	5	3	4	1	1	1
VOC% (EPA) - Aerosol	73	64	64	-	37	75	75	-	-	-
VOC% (EPA) - Bulk	95	-	-	61	49	100	-	45	22	52
VOC% (CARB) - Aerosol	70	75	75	-	75	75	75	-	-	-
VOC% (CARB) - Bulk	100	-	-	100	100	100	-	45	52	22
kB Values	100	83	83	78	54	-	87	-	-	-
APPLICATIONS										
Benchtop cleaning	●	●	●	●	●	●	●			
Ultrasonic	●		●	●	*	●	+	+	+	+
Vapor degreasing	●			●						
Inline defluxing system							●	●	●	●
Batch defluxing system							●	●	●	●

NOTE: Test for substrate compatibility as a part of your qualification process.

* Non-heated ultrasonic only + Rinse required

Solvent Defluxers



Flux Remover

Powerful, nonflammable and cost effective cleaner

Cleans away flux residues and other contaminants in vapor cleaning and ultrasonic application. Easily removes residues from high temperature lead free soldering operations, no-clean fluxes and all handling soils.

3401-G	1 gal. (3.8L) pail
3401-5G	5 gal. (18.9L) pail
3401-54G	54 gal. (204L) drum



- Nonflammable
- Much safer than most common industrial solvents — TCE, nPB, Perc & Methylene Chloride
- Powerful cleaner - Effective on R, RMA & no-clean fluxes
- Available in bulk for vapor degreasing, ultrasonic and immersion cleaning
- Rapid evaporation
- Non-ozone depleting



Flux Remover

Strong and fast-acting flux remover

Remove flux residues and other contaminants left by manufacture, rework, or repair of printed circuit boards.

1631-5S	5 oz. (142g) aerosol w/brush attachment
1631-16S	16 oz. (454g) aerosol
1631-16SB	16 oz. (454g) aerosol w/brush attachment



- Nonflammable
- Powerful cleaner
- Proven effective for lead-free processes
- All-in-one cleaner and defluxer
- Rapid evaporation
- Non-ozone depleting



No-Clean Flux Remover

Strong and fast-acting no-clean flux remover

Remove no-clean flux and white residues left by manufacture, rework, or repair of printed circuit boards.

1634-12S	12 oz. (340g) aerosol
-----------------	-----------------------



- Nonflammable
- Ideal for no-clean fluxes
- Proven effective for lead-free processes
- Rapid evaporation
- Non-ozone depleting



Universal Cleaner

Nonflammable, powerful liquid cleaner

Engineered to remove oils, fluxes and other contamination from electronics using a manual soak cleaning process or ultrasonic equipment.

1638-G	1 gal. (3.8L) pail
1638-5G	5 gal (19L) pail
1638-54G	54 gal. (205L) drum



- Nonflammable
- Powerful cleaner
- Effective as maintenance cleaner and flux remover
- Rapid evaporation
- Non-ozone depleting
- Dielectric strength – 27.3 kv



TECHSPRAY®

Precision V**Flux Remover & Maintenance Cleaner***Nonflammable and powerful precision cleaner*

Formulated to reduce VOCs within your facility. Ideal for aviation and other applications where strict VOC caps apply (based on EPA VOC exemptions). Bulk chemicals ideal for soak cleaning and ultrasonics (not intended for vapor degreaser).

- Nonflammable
- Low VOC
- High precision – residue-free
- Rapid evaporation
- Non-ozone depleting
- Safe on most plastics

1651-16S 16 oz. (454g) aerosol
1651-5G 5 gal. (19L) pail



1651-16S

***E-Line*****Flux Remover & Maintenance Cleaner***Powerful and economical flux remover*

Hydrocarbon-based defluxer formulated to be powerful, yet very economical. Eliminates brushing and scrubbing, saving time and materials.

1621-10S 10 oz. (283g) aerosol
1621-10SB 10 oz. (283g) aerosol w/brush attachment
1621-G 1 gal. (3.8L) can
1621-5G 5 gal (19L) pail
1621-54G 54 gal (205L) drum



- Powerful cleaner
- Proven effective for lead-free processes
- Ideal for sensitive plastics

Specifications: GM H1013; Ford Tox #142431,
USDA: NSF registered K-2 aerosol and bulk.



TECHSPRAY®

PRECISIONV



Vapor Degreaser Solvents

Techspray offers a wide variety of vapor degreaser formulas engineered to meet challenging requirements like cleanliness specifications, difficult-to-clean soils, solvent-sensitive materials, and restrictive regulations.

All Techspray solvents have azeotropic properties that allow them to remain stable as they are cycled in a vapor degreaser. They are not reactive or corrosive to metals commonly found in the construction of vapor degreasers.

PWR-4™ solvents are designed to replace nPB, TCE and Perc, matching and surpassing cleaning performance without the safety concerns.

Precision-V™ vapor degreaser solvents are ideal replacements for AK-225 based cleaners, which were phased out due to the ozone depletion restrictions of the Montreal Protocol.

To order, add the following to the part # shown in the chart below:

- 1G for 1 gal. (3.8L)
- 5G for 5 gal. (19L)
- 54G for 54 gal. (205L)



Part #	Product Name	Base Solvents	kB value	Boiling Point (°F/°C)	VOC (g/l)	GWP	Degreasing	Defluxing	Plastic-Safe
1654	VC-1200	DuPont Vertrel® XF	56	94/34	552	684	●		
1655	VC-1500	DuPont Vertrel® XF	62	90/32	562	663		●	
1656	VC-1600	DuPont Vertrel® XF	100	106/41	1063	264		●	
1686	ME-1500	3M Novec 7100/7200	58	104/40	889	43	●	●	
1680	AE-1000	Asahi AE3000	~0	133/56	ND	540			●
1681	AE-1400	Asahi AE3000	ND	139/54	ND	540	●	●	●
3400	PWR4 Maintenance Cleaner	3M Novec 7100	100	118/48	1201	ND	●		
3401	PWR4 Flux Remover	3M Novec 7100	100	118/48	1201	ND		●	

ND=Not Defined



Water-Based Defluxers

Eco-dFluxer

Water-based Inline & Batch Flux Removers

Eco-dFluxer cleaners are water-based, environmentally friendly and designed to work in both inline and batch cleaning equipment. They are optimal combinations of solvents and saponifiers that lower surface tension for penetration under low stand-offs, and powerful cleaning action to remove all flux residues.

Effective on a wide variety of solders and fluxes: lead, lead-free, aqueous, RMA, no-clean, and new halide-free fluxes. High compatibility with common PCB metals and plastics. Eco-dFluxer cleaners are highly filterable with long bath life.

High performance cleaning gives you brilliant solder joints and allows you to increase dilution, increase line speeds, reduce waste water, decrease cost per board, and most importantly... eliminate field failures due to ionic contamination!

- **High performance cleaning**
- **Nonflammable**
- **Low VOC, zero GWP**
- **Also used for pallet cleaning in batch systems**

Eco-dFluxer SMT100

Powerful defluxer, allowing you to optimize your cleaning process. Reduce concentration and increase line speed to maximize your profit. Effective on no-clean, R, RMA and OA fluxes.

1550-G	1 gal. (3.8L) bottle
1550-5G	5 gal. (19L) container
1550-54G	54 gal. (205L) drum

Eco-dFluxer SMT200

Superior metals compatibility, preventing oxidation and leaving shiny solder joints. Eco-friendly formula reduces shipping and disposal costs. Effective with reduced concentration even on the toughest no-clean, R, RMA, OA and new halide-free fluxes.

1520-G	1 gal. (3.8L) bottle
1520-5G	5 gal. (19L) container
1520-54G	54 gal. (205L) drum



Eco-dFluxer SMT300

Powerful defluxer but safe on sensitive metals, preventing oxidation and leaving shiny solder joints. Safe, eco-friendly formula. Effective on no-clean, R, RMA, OA fluxes and new halide-free fluxes.

1530-G	1 gal. (3.8L) bottle
1530-5G	5 gal. (19L) container
1530-54G	54 gal. (205L) drum

Defoamer DF1

Defoaming Agent for Inline & Batch Cleaners

Reduce foaming as cleaner becomes loaded to extend bath life. Add directly to sump at 1 to 4 fl oz. (30-120ml) per 100 gallons (379L). Dilute in spray bottle to 15% with DI water to eliminate foaming issue on the spot.

- Effective at all processing temperatures
- Extends bath life
- Silicone & particulate free
- Nonflammable

1555-P	1 pt. (473mL) container
---------------	-------------------------





Stencil Cleaners

Eco-Stencil UM

Manual & Under Stencil Cleaner

- Quickly clean paste or uncured adhesive
- Safe for stencils, tools, misprinted boards
- Nonflammable
- Low VOC, zero GWP

Applications:

- Manual stencil tool, work surface, and squeegee cleaning
- Automatic underside wipe stencil cleaning
- Batch ultrasonic cleaning
- Removes unsoldered leaded & lead-free solder pastes
- Cleans off uncured adhesives

1570-100DSP 100 count pre-saturated wipes, 6"x8" (15cm x 20cm)

1570-QT 1qt. (0.95L) w/ trigger sprayer

1570-G 1 gal. (3.8L) bottle

1570-54G 54 gal. (205L) drum



Specification: Compliant with Speedline / ITW EAE compatibility criteria for Accelta, Momentum and MPM 125 printers.

Eco-Stencil RF

Rinse-Free Batch Stencil Cleaner

1571-G 1 gal. (3.8L) bottle
1571-5G 5 gal. (19L) container



- Nonflammable
- Rinse-free
- Drop in replacement for IPA
- Effective at ambient temperature
- Low VOC, zero GWP
- Highly concentrated - 20% dilution

SMT Equipment Maintenance

Eco-Oven

Reflow Oven, Wave Finger & Pallet Cleaner

- Quickly clean flux residue from oven & wave fingers
- Safe on warm ovens
- Nonflammable
- Low VOC, zero GWP


Applications:

- Removal of baked-on flux residues from SMT oven and wave equipment
- Maintenance cleaning for heat exchange systems (*NOTE: rinse thoroughly from aluminum and copper*)
- Finger cleaning in wave solder equipment
- Remove accumulated flux from wave solder pallets

1573-QT 1 qt. (0.95L) w/ trigger sprayer

1573-G 1 gal. (3.8L) bottle

1573-5G 5 gal. (19L) container



Wave finger cleaning



TECHSPRAY®

ESD Products



LICRON CRYSTAL™

Permanent ESD Coating

- Rugged static dissipative coating
- Surface resistivity of 10^6 To 10^9 ohms
- Operating temperature range – up to 302°F (155°C)
- Humidity independent
- Superior adhesion to variety of surfaces: glass, plastic, etc.
- Non-ozone depleting

1756-8S 8 oz. (226g) aerosol (coats up to 200ft²)

1756-G 1 gal. (3.8L) jug

1756-5G 5 gal. (19L) pail

1756-54G 54 gal. (204L) drum



1756-8S

Zero Charge Anti-Stat Coating

Anti-static coating for fabrics & flexible surfaces

- All-purpose static control
- For plastics, fabrics, and carpet
- Fast drying
- Nonflammable

1726-QT 1 qt. (.95L) bottle with trigger sprayer



1726-QT

Zero Charge® ESD-Safe Floor Coating

ESD-safe floor coating

- Resistivity between 10^6 To 10^{10}
- Effective in low humidity
- High gloss polymer
- Zinc free
- Slip resistant

1720-G 1 gal. (3.8L) bottle (coats @1,200 ft²)

1720-G

Zero Charge Screen & Keyboard Cleaner

Cleans surfaces and leaves behind dissipative residue

1743-50PK 50 pre-saturated wipes in packets

1743-QT 1 qt. (.95L) bottle
w/trigger sprayer

1743-50PK

Zero Charge Mat & Tabletop Cleaner

Safe, effective cleaner for ESD mats

- Rejuvenates ESD-safe mats
- Will not dry out surfaces
- Leaves no insulative film
- Nonflammable
- No ammonia
- Non-corrosive

1733-QT 1 qt. (.95L) bottle with trigger sprayer

1733-G 1 gal. (3.8L) bottle



1733-QT

Zero Charge Hand Lotion

Non-contaminating hand lotion for ESD sensitive environments

- Improves wrist and heel strap contact
- Does not contain silicone or lanolin
- Non-contaminating — does not interfere with soldering
- Non-greasy

1702-8FP 8 fl. oz. (237ml) bottle with finger pump

1702-G 1 gal. (3.8L) bottle



1702-8FP



1743-QT

- Cleans plastic & glass
- Leaves ESD-safe coating
- Leaves no insulative film
- Nonflammable
- Non-corrosive



Conformal Coatings

Techspray offers a variety of coating formulas to match field and engineering requirements. Specifications generally depend on the type of protection needed: e.g. thermal, moisture, and static resistance (see reference chart on the next page).

Application method considerations:

Dip – High volume method to fully coat boards. Thickness of final coating is controlled by viscosity and withdrawal speed from the pot.

Selective spray system – Computer controlled selective spray systems, eliminate the need for masking. Higher viscosity than full coverage sprayer is generally needed (70-200 cps) to create precise edge definition and prevent splattering.

Manual Application – Aerosol and brushing are generally used for small production runs, rework and repair. If using for rework, the aerosol needs to be compatible with the original coating.



FINE-L-KOTE™ SR

Silicone coating that's ideal for moisture and vibration protection

Standard Viscosity — 4-10 CPS

Coverage (1 mil dry film):

1 aerosol can - 16 ft² (1.5 M²)

1 gal. liquid - 224 ft² (20.8 M²)

2102-12S 12 oz. (355ml) aerosol

2102-P 1 pt. (473mL) can

2102-G 1 gal. (3.8L) can

2102-5G 5 gal. (19L) pail

High Viscosity — 60-90 CPS

2102-GHV 1 gal. (3.8L) pail



2102-12S

- UL recognized
- Thermal resistance — to 392°F (200°C)
- Dielectric strength — 1100 volts/mil
- Moisture resistant
- Chemically resistant
- Vibration resistant — flexible

Specifications: Meets or exceeds MIL-I-46058C Type SR and IPC-CC-830B. UL94 V-0 rated.



FINE-L-KOTE™ HT

Silicone coating engineered for superior thermal and moisture resistance

Coverage (1 mil dry film):

1 aerosol can - 20 ft² (1.9 M²)

1 gal. liquid - 880 ft² (81.8 M²)

2106-12S 12 oz. (355ml) aerosol

2106-G 1 gal. (3.8L) can



2106-12S

- Designed for high temperature environments

• Fast-drying silicone – 1-step process

• Thermal resistance – to 662°F (350°C)

• Dielectric strength – 560 volts/mil

• Moisture resistant

• Vibration resistant – flexible

Specifications: Meets or exceeds MIL-I-46058C Type SR and IPC-CC-830B. UL94 V-0 rated.

FINE-L-KOTE™ LED

Silicone conformal coating designed to coat over LEDs

Coat directly over LEDs without the time and expense of masking. Optical clarity prevents light from diffusing, scattering, or changing wavelength. Fine-L-Kote LED provides maximum protection from extreme temperatures on the flexible and rigid PCBs found in LED displays.

Coverage (1 mil dry film):
1 gal. liquid - 880 ft² (81.8 M²)

2120-P 1 pt. (473mL) can
2120-G 1 gal. (3.8L) can
2120-5G 5 gal. (19L) pail



- Fully transparent - will not block or change light intensity or wavelength
- Protects against adverse environments
- Flexibility prevents cracking
- Resists moisture, salt, fungus and corrosive vapors from severe environments
- Withstands high heat from PCB and operating environment

CONFORMAL COATING SELECTION GUIDE

	2102 Fine-L-Kote SR	2103 Fine-L-Kote AR	2104 Fine-L-Kote UR	2106 Fine-L-Kote HT	2108 Turbo-Coat	2109 Turbo-Coat HV	2120 Fine-L-Kote LED
Product Benefits	Moisture & Vibration Resistant	Economical	Durable & Chemically Resistant	High Operating Temperature	Economical With Fastest Cure	Economical With Fastest Cure	Optically Clear
Selective Spray System	●	○	●	●	●	●	●
Atomized Spray System	●	○	●	●	●	●	●
Dip	●	○	●	●	●	●	●
Aerosol Available	YES	YES	YES	YES	YES	USE 2108-12S	NO
Thermal Resistant	●	●	●	●	●	●	●
Moisture /Fungus Resistant	●	●	●	●	●	●	●
Chemical Resistant	●	○	●	●	○	○	●
Vibration Resistant	●	●	○	●	●	●	●
Ease of Rework	●	●	●	●	●	●	●
Tack Free Time (minutes)	60	15	15	45	3	9	60
Accelerated Cure Time/Temp	2 Step 30 Min. @ 32°C 45 Min. @ 93°C	2 Step 20 Min. @ 120°F 30 Min. @ 180°F	2 Step 20 Min. @ 49°C 30 Min. @ 82°C	1 Step 15 Min. @ 49°C	1 Step 20 Min. @ 65°C	1 Step 55 Min. @ 55°C	2 Step 30 Min. @ 32°C 45 Min. @ 93°C
Ambient Cure Time Mil-I-46058C /	72 Hrs.	24 Hrs.	24 Hrs.	24 Hrs.	<15 Hrs.	<15 Hrs	72 Hrs.
IPC-CC-830 Qualified	YES	NO	YES	YES	YES	YES	
UL 94 Rated	V-0		V-0	V-0	V-0	V-0	
Solids Content (% by weight)	Aerosol 11% Bulk 14%	6.1%	Aerosol 7% Bulk 20%	Aerosol 16% Bulk 25%	Aerosol 7% Bulk 17%	Bulk 24%	47%
Viscosity (centipoise)	Aerosol 4-10 Bulk 4-10	Aerosol 22	Aerosol 12-22 Bulk 10-20	Aerosol 15-25 Bulk 15-25	Aerosol 10-20 Bulk 15-25	Bulk 55-60	Bulk 60-70
UV Indicator	YES	YES	YES	YES	YES	YES	NO
Operating Temp Range	-65° to 200°C	-65° to 125°C	-30° to 121°C	-40° to 350°C	-65° to 125°C	-65° to 125°C	-65° to 200°C
Dielectric Strength	1.1 kV/Mil	2086 kV	380 V/Mil	560 V/Mil	1 kV/Mil	1 kV/Mil	1 kV/Mil
Dielectric Constant	2.66	3.1	3.8	2.5			
Insulation Resistance (ohms)	6.87×10^{15}	4×10^{13}	1.78×10^{16}	1.33×10^{16}	4.89×10^{16}	4.89×10^{16}	
VOC	Aerosol 46% Bulk 58%	Aerosol 29%	Aerosol 52% Bulk 54%	Aerosol 51% Bulk 79%	Aerosol 33% Bulk 64%	Bulk 7%	Bulk 54%

Key: ● = Best ○ = Acceptable ○ = Not applicable / Not recommended



TECHSPRAY®



TURBO-COAT™

Acrylic Conformal Coating

Coverage (1 mil dry film):

1 aerosol can - 14 ft² (1.3 M²)

1 gal. liquid - 272 ft² (25.3 M²)

2108-12S 12 oz. (355ml) aerosol

2108-P 1 pt. (473mL) can

2108-G 1 gal. (3.8L) can

2108-5G 5 gal. (19L) pail



2108-12S

- Fastest cure – dry to touch in 3 minutes!

- Low toxicity

- No Toluene, Xylene or MEK

- UL94 V-0 rated – nonflammable final coat

- Fast & easy rework & repair

- UV indicator for black light

- QC inspection

Specifications: Meets or exceeds MIL-I-46058C

Type AR and IPC-CC-830B. UL94 V-0 rated.

TURBO-COAT HV™

Acrylic Conformal Coating

Coverage (1 mil dry film):

1 gal. liquid - 391 ft² (36.3 M²)

2109-P 1 pt. (473mL) can

2109-G 1 gal. (3.8L) can

2109-5G 5 gal. (19L) pail



2109-G

2109-5G

- Designed for selective sprayers

- Low toxicity

- No Toluene, Xylene or MEK

- Dry to touch in under 10 minutes!

- UL94 V-0 – nonflammable final coat

Specifications: Meets or exceeds MIL-I-46058C

Type AR and IPC-CC-830B. UL94 V-0 rated.

FINE-L-KOTE™ AR

Acrylic Conformal Coating

Coverage (1 mil dry film):

1 aerosol can - 12 ft² (1.1 M²)

2103-12S 12 oz. (355ml) aerosol



2103-12S

- Fast & easy rework & repair

- UV indicator for black light QC inspection

FINE-L-KOTE™ UR

Urethane Conformal Coating

Coverage (1 mil dry film):

1 aerosol can - 10 ft² (0.9 M²)

1 gal. liquid - 320 ft² (29.7 M²)

2104-12S 12 oz. (355ml) aerosol

2104-G 1 gal. (3.8L) can

2104-5G 5 gal. (19L) pail



2104-12S

- Thermal resistance – to 248°F (120°C)

- Dielectric strength – 380 volts/mil

- Moisture resistant

- Chemically resistant

- Abrasion resistant

- UL94 V-0 – nonflammable final coat

Specifications: Meets or exceeds MIL-I-46058C

Type UR and IPC-CC-830B. UL94 V-0 rated.

Conformal Coating Remover

Quickly and precisely removes most conformal coatings including acrylic, urethane, and silicone.

- Fast stripping action

- Non-corrosive

- Rapid evaporation



2510-N

2510-N 10 ml pen

2510-P 1 pt. (473mL) can



2510-P

FINE-L-KOTE™ Thinner

Thin Fine-L-Kote coatings to meet production requirements.

2105-G 1 gal (3.8L) can



Turbo-Coat Thinner

Thinner ideally matched to Turbo-Coat coatings

2110-P 1 pt. (473mL) can



Temporary Solder Masks

Techspray's WonderMASK is the industry leading temporary solder mask brand because of quality and versatility. Depending on the product, mask can be peeled off manually, or washed off in a batch or inline system.

All Techspray WonderMASK products have the following advantages:

- **Can be cured in pre-heat**
- **Withstands lead-free soldering temperatures up to 640°F (343°C) in wave soldering process**
- **RoHS compliant**

Washable Masks *Used with aqueous cleaning processes.*

WonderMASK WSOL

Water-washable mask, safe on ion beds and filters

Ideal water-washable mask for closed-loop systems. Quickly and easily removed with in-line and batch cleaning system.

2204-8SQ 8 fl. oz. (237mL) squeeze bottle
2204-G 1 gal. (3.8L) bottle



- 100% Water-soluble
- Safe on ion beds & filters in closed-loop cleaning systems
- Non-corrosive
- Low odor

2204-8SQ

WonderMASK W

Nonflammable, water-washable

Quick drying water-washable mask. Quickly and easily removed with in-line and batch cleaning systems.

Note: do not use in closed-loop wash systems.

Hand Applications:

2205-8SQ 8 fl. oz. (237mL) squeeze bottle
2205-G 1 gal. (3.8L) bottle

Robotic & Pneumatic Applications:

2206-G 1 gal. (3.8L) bottle



- Water washable
- Non-corrosive
- Low odor
- Nonflammable

Specifications: Meets MIL-STD-2000 paragraph 5.3.18 parts a,b, and d. (2206) HP 8500-4214

2205-8SQ

TEMPORARY SOLDER MASK SELECTION GUIDE

PRODUCT	APPLICATION	VISCOSITY	SUGGESTED THICKNESS	THINNER	CURE TIME	REMOVAL
PEELABLE						
2211 WonderMASK P	Template, Hand, Pneumatic, Robotic	28,000 – 32,000 cps	20 – 30 mils	D.I. Water	1 hr. Ambient 30 min. @65°C 20 min. @82°C	Peelable
2222 WonderMASK PX	Hand Applied	9,000 – 16,000 cps	15 mils	D.I. Water	15 min. Ambient	Peelable
TC-533 Techform	Hand Applied	9,000 – 15,000 cps	15 mils	D.I. Water	1 hr. min. Ambient 30 min. @65°C	Peelable
WATER-SOLUBLE						
2204 WonderMASK WSOL	Hand, Pneumatic	11,500 – 15,500 cps	5 – 15 mils	Methanol	30 min. @65°C	Soluble in Water 49°C or higher
2205 WonderMASK W	Hand Applied	8,000 – 12,000 cps	10 – 15 mils	D.I. Water	30 min. @80°C 1-2 hrs. Ambient	Soluble in Water 49°C or higher
2206 WonderMASK W	Pneumatic, Robotic	6,050 – 6,450 cps	10 – 15 mils	D.I. Water	1-2 hrs. Ambient 30 min. @80°C	Soluble in Water 49°C or higher



Peelable Masks *Used with solvent cleaning and no-clean processes.*

WonderMASK PX

Natural latex peelable solder mask with fastest cure time.


Natural latex temporary solder mask that is specially formulated to cure in half the time of other masks.

WonderMASK PX cures over its entire surface area, including where it adheres to the PCB. This allows it to be peeled quickly and easily when other masks are still sticky at the bottom. Even the thickest bead of mask cures completely.

Specifications: Meets MIL-STD-2000 paragraph 5.3.18 parts a, b, and d.

- Fastest full cure
- Easily peelable
- Highest strength to avoid breakage
- Nonflammable

2222-8SQ 8 fl. oz. (237ml) squeeze bottle
2222-G 1 gal. (3.8L) bottle



WonderMASK PX peels after 15 min.



Typical mask after 15 min.

WonderMASK P

Non-ammoniated, low odor peelable mask

Techspray's original ammonia-free synthetic latex peelable solder mask.

Specifications: MIL-STD-2000 paragraph 5.3.18 parts a,b, and d. Ford Tox #039772.

2211-8SQ 8 fl. oz. (237mL) squeeze bottle
2211-G 1 gal. (3.8L) bottle
2211-5G 5 gal. (19L) pail
2211-54G 54 gal. (205L) drum



- Easily peelable
- Low odor
- Cure indicator – darkens as it cures
- Compatible with gold and copper leads
- Non-corrosive
- Nonflammable



Techform TC-533 Peelable Mask

Kester peelable mask is a high-temperature flexible solder masking compound specially formulated of natural latex rubber. Prevent solder from flowing into contacts, terminals, screw heads and plated through holes.

Latex has been chemically enhanced so that it is heat stable enough for wave soldering processes. Effectively mask and protect the board from the time it is manufactured, through all assembly and reflow operations.

NOTE: Not recommended on bare copper because ammonia may cause discoloration.

- Fast cure
- Easily peelable
- Will not tarnish gold or phosphor bronze
- Protects delicate components
- Nonflammable

53-4001-0533
1pt. (0.47L) squeeze bottle

53-4003-0533
1 gal. (3.8L) bottle

53-4004-0533
5 gal. (19L) pail





TECHSPRAY®

Freeze Sprays

Freeze sprays blast fast evaporating liquid that super-chills isolated areas. Used as a troubleshooting aid for intermittently faulting capacitors, resistors, semiconductors, and other defective components. They also increase visibility of cold solder joints, cracks in printed circuit boards and oxidized junctions.

- Nonflammable
- Safe on plastics
- Zero residue
- Moisture free
- Non-ozone depleting
- VOC exempt

Freeze Spray

Pure HFC-134a freeze Spray

- Chills down to -60°F (-51°C)
- Nonflammable
- Safe for energized equipment

1672-10S 10 oz. (283g) aerosol
1672-15S 15 oz. (425g) aerosol

CAN1672-10S 10 oz. (283g) aerosol

Canada compliant packaging



Anti-Static Freeze Spray (▲)

ESD-Safe Diagnostic Freeze Spray

1747-10S 10 oz. (283g) aerosol



- Avoids static build-up
- Prevents latent failures
- Chills down to -60°F (-51°C)
- Nonflammable
- No frost buildup

Eco-Freezer

Eco-Friendly Freeze Spray

Eco-Freezer is formulated with new HFO-1234ze propellant, with a fraction of the global warming potential (GWP) of HFC-134a based freeze sprays. HFO-1234ze has a GWP of 6, compared to HFC-134a with GWP of 1300. Eco-Freeze can be a drop-in replacement when GWP needs to be lowered.

1583-10S 10 oz. (283g) aerosol

- Chills down to -49°F (-45°C)
- GWP less than 1/100th of HFC-134a
- Nonflammable
- Non-ozone depleting



TECHSPRAY®

Desoldering Braid

Desoldering braid (wick) is pre-fluxed copper braid that is used to remove solder, which allows components to be replaced and excess solder to be removed.

Techspray wick is available in static dissipative bobbins (except where indicated) for static sensitive environments.


Techspray No-Clean wick is coated with proprietary flux that only leaves a slight clear residue, which does not cause service issues. Cleaning after using Techspray No-Clean wick is strictly optional.

Specifications: Meets or Exceeds MIL-F-14256; NASA NHB 5300, 4 (34-1); NASA NPC 200-4; NASA SP5002; 1821:HP 8690-0588; 1823: HP 8690-0577; IPC Standard-J-STD-004

DESOLDERING BRAID SELECTION CHART

#1 White	#2 Yellow	#3 Green
.035" (0.9mm)	.055" (1.4mm)	.075" (1.9mm)
#4 Blue	#5 Brown	#6 Red
.098" (2.5mm)	.130" (3.3mm)	.193" (4.9mm)

Wick in selection chart shown actual size.



Pro-Wick® Rosin — ESD-Safe Bobbin

For the fastest wicking action, rosin flux coated braid is ideal for high volume PCB production/repair environments.

	Size/Color	5'	10'	25'	100'	500'
1808	#1 White	1808-5F	1808-10F	—	1808-100F	—
1809	#2 Yellow	1809-5F	1809-10F	1809-25F	1802-100F*	1802-500F*
1810	#3 Green	1810-5F	1810-10F	1810-25F	1810-100F	1803-500F*
1811	#4 Blue	1811-5F	1811-10F	1811-25F	1811-100F	1804-500F*
1812	#5 Brown	1812-5F	—	—	1805-100F*	—
1813	#6 Red	1813-5F	—	—	1806-100F*	—

* Not packaged in ESD-safe bobbins

No-Clean Wick — ESD-Safe Bobbin

The cleanest No-Clean braid in the industry. The proprietary flux formula is specially designed to avoid catastrophic and latent PCB failures caused by ionic flux residue.

	Size/Color	5'	10'	25'	50'	100'
1820	#1 White	1820-5F	1820-10F	—	1820-50F	—
1821	#2 Yellow	1821-5F	1821-10F	1821-25F	1821-50F	—
1822	#3 Green	1822-5F	1822-10F	—	1822-50F	1822-100F
1823	#4 Blue	1823-5F	1823-10F	1823-25F	—	1823-100F
1824	#5 Brown	1824-5F	—	1824-25F	—	—
1825	#6 Red	1825-5F	—	—	—	—



Unfluxed Wick — ESD-Safe Bobbin

For customers who use water-soluble flux, or their own flux for aqueous processes.

	Size/Color	5'	10'
1830	#1 White	—	1830-10F
1831	#2 Yellow	—	1831-10F
1832	#3 Green	1832-5F	—
1833	#4 Blue	—	1833-10F



Match braid width to contact area



Rework & Repair Pens

TraceTech™

Flux Remover Pen

Spot cleaning for PCB rework and repair

2506-N Single-pack of 11.5 ml pen



- Safe on plastics
- Rapid evaporation
- Pen tip allows controlled application

TraceTech™

No-Clean Flux Dispensing Pen

No-clean flux applicator pen for PCB rework and repair

2507-N Single-pack of 11.5 ml pen

2507-N100 144 pack of 11.5 ml pens, 12 boxes of 12



- Excellent wetting
- Works with lead and lead-free solders
- Boosts wetting for lead-free wire solder
- No cleaning necessary

TraceTech™

Conductive Pen

Silver ink pen for repairing electronic traces

2505-N Single-pack of 4.9 ml pen



- Repairs traces
- Makes smooth jumpers

TraceTech™

Overcoat Pen

Resist repair pen for PCB rework and repair

2509-GN Single-pack of 5 ml pen



- Repairs solder resist
- Green to match resist
- Prevents shorting and arcing

TraceTech™

Conformal Coating Remover Pen

Spot coating remover in applicator pen for PCB rework and repair

2510-N 10 ml pen

2510-P 1 pt. (0.47L) can



- Fast stripping action
- Non-corrosive
- Rapid evaporation

Heat Sink / Transistor Grease

Silicone Heat Sink Compound

Heat sink compound for electrical applications

1977-DP 4 oz. (118ml) squeeze tube



- Thermal conductivity – 0.70 W/m-K
- Functional temperature Range
-67°F to 401°F (-55°C to 205°C)
- Easy application
- Will not harden and crack

Silicone-Free Heat Sink Compound

Heat-sink for electronics, avoid silicone contamination

1978-DP 4 oz. (118ml) squeeze tube

1978-1 1 lb. (454g) jar



- Thermal conductivity – 0.92 W/m-K
- Functional temperature range -40°F to 392°F (-40°C to 200°C)
- Avoid solder defects due to silicone contamination
- Easy application
- Will not separate
- Will not harden and crack



Wipes

Techspray offers a large array of wipes for a variety of applications, including cleanroom, PCB rework, polishing, and maintenance. A large number of different materials are available to meet each unique requirement.

- Cleanroom Wipers:** Meet the particulate count and extractables for Class 10 / ISO Class 4 and Class 100 / ISO Class 5 cleanrooms.

CLASS
10 CLASS
100

- Maintenance Wipers:** Lower cost, high quality wipers for heavy-duty cleaning.

- Delicate Task Wipers:** Cellulose tissue for light cleaning, like in lab settings.

- Microfiber Wipes:** Polishing wipes that are ideal for screen and display cleaning, with or without a cleaner.

- SMT Roll Wipes:** DEK and MPM understencil roll wipes to fit the most common printers.



TECHCLEAN® WIPES SELECTION GUIDE

Key: ● = Best ○ = Acceptable ○ = Not applicable / Not recommended

	Cleanroom	Properties				Application							
		Material	Construction	Absorbency	Strength	Electronics	ESD-Sensitive	LCD Cleaning	Stencil Cleaning	Lab	Optics	Industrial	Office
2340 Cotton Wiper		Cotton	Non-woven	●	○	●	○	○	●	●	○	●	●
2342/2343 Task Wipers	n/a	Poly / Cellulose	Non-woven	○	○	●	○	○	○	●	●	○	○
2350 Wiper	100 / ISO 5	Poly / Cellulose	Non-woven	●	○	●	○	○	●	●	○	●	●
2351/2352 Absorbwipe	100 / ISO 5	Polyester	Non-woven	○	○	●	○	○	○	○	●	○	○
2355 Purewipe	100 / ISO 5	Polyester	Knit	○	●	●	○	●	●	●	○	●	●
2357 Twill Wipe	n/a	Cotton	Woven	●	●	○	○	○	○	○	○	●	○
2358 SMT Wipe	100 / ISO 5	Poly-urethane	Foam	●	○	○	○	○	●	○	○	○	○
2359/2364/2365 Maintenance Wipe	n/a	Poly / Cellulose	Non-woven	●	○	○	○	○	●	●	○	●	●
2362 Antistatic Wipe	10 / ISO 4	Polyester	Knit	○	●	●	●	●	○	●	○	○	○
2363 Microfiber Wipe	n/a	Poly / Nylon	Knit	○	●	○	○	●	○	○	●	○	●
2366/2367 Roll Wipes	n/a	Poly / Cellulose	Non-woven	●	○	○	○	○	●	○	○	○	○
2368 LCD Wipe	n/a	Nylon	Knit	○	●	○	○	●	○	●	●	●	●

Note: To qualify for your cleanroom requirements, please refer to www.techspray.com for full data sheets.



TECHSPRAY®



TechClean Wiper CLASS 100

General Purpose Wipe

Hydroentangled cellulose/polyester wipe with high absorbency and extra low particulate count and no chemical extractables.

2350-100 100 - 8"x10" (20cm x 25cm) c-fold wipes,
double-bagged



- Class 100 cleanroom qualified
- High absorbency

• Very low particulate count

Specifications: Exceeds U.S. Air Force requirements for surface contamination, HP 9300-1618

TechClean Purwipe™ CLASS 100

Low-Linting Poly Wipe

100% polyester wipe is a strong, low-linting wipe that is ideal for SMT stencil cleaning and PCB rework. Tear resistant to allow cleaning around leads without fraying.

2355-100 100 - 9"x9" (23cm x 23cm) flat wipes, double-bagged



- Class 100 cleanroom qualified

• Very low particulate count

• Tear resistant

Cotton Cleanroom Wiper

This hydroentangled cotton wipe has high absorbency with extra low particulate and chemical extractables. Ideal for stencil cleaning.

2340-100 100 - 9" x 9", (23cm x 23 cm),
flat wipes, double-bagged



- Low chemical extractables
- Lint-free & soft
- Biodegradable & sustainable
- High absorbency - 6 times its weight
- Made with USA grown cotton

Recycled Delicate Task Wipers

Ideal for light cleaning tasks in the laboratory, repair and maintenance facilities, and more. Quickly and easily wipes up liquid and dust. Packaged in a portable dispenser that reduces lint and cross contamination.

2342-300 280 count, 4.4"x 8.3" (11cm x 21cm),
pop-up box, 60 boxes/case



- Low linting
- Eco-friendly replacement for Kimwipes (KC34155, KC34256)
- 100% recycled wipe & box
- Biodegradable & sustainable

TechClean Absorbwipe™ CLASS 100

For Sensitive Surfaces

Very soft and absorbent hydroentangled polyester wipe for cleaning optical equipment, fiber optics, and other sensitive surfaces.

2351-100 100 - 4"x4" (10cm x 10cm) flat wipes, double-bagged

2352-100 100 - 9"x9" (23cm x 23cm) flat wipes, double-bagged



- Non-abrasive
- Extremely soft
- Highly absorbent

TechClean Maintenance Wipes

Hydroentangled cellulose/polyester wipe with high absorbency. Economical, but very high quality wipes are ideal for production and maintenance applications.

2359-300 300 - 9"x9" (23cm x 23cm) flat wipes



- High absorbency
- Economical

Economy Grade

2364-50 50 - 12"x 12" (30.5cm x 30.5cm) dry wipes

2365-300 300 - 9"x 9" (23cm x 23cm) dry wipes



Anti-Static Wipe CLASS 10

Polyester wipe that is interwoven with DuPont's NEGA-STAT carbon yarn. NEGA-STAT dissipates static charge, preventing static buildup and allowing dissipation. Perfect for dry wiping ESD-sensitive components and boards. Tear resistant to allow cleaning around through-hole leads without fraying.

2362-150 150 - 9"x9" (23cm x 23cm) flat wipes

2362-4X4-200 200 - 4" x 4" (10.2cm x 10.2cm) flat wipes, double-bagged



- Anti-static — will not generate charge
- Class 10 cleanroom laundered & qualified
- Tear resistant

TechClean Twill Wipe

Tear Resistant Cotton

100% cotton twill weave designed for wiping abrasive surfaces. Tear resistant to allow cleaning around leads without fraying. Low static generation, so good for static sensitive areas.

2357-100 100 - 6"x6" (15cm x 15cm) flat wipes, double-bagged



- Tightly woven 100% cotton
- Tear resistant
- Low static generation

TechClean SMT Wipe CLASS 100

Lint-Free Foam

Polyurethane foam wipe designed for cleaning surface mount stencils and screening equipment. Fiber-free foam does not generate lint, which can clog fine pitched stencils and cause misprints.

2358-50 50 - 9"x9" (23cm x 23cm) flat wipes, double-bagged



- Class 100 cleanroom qualified
- Fiber-free construction — no linting
- Will not snag on stencils
- Tear resistant

Microfiber Glass & Plastic Cleaning Wipes

Cleans and polishes glass or plastic. Ideal for removing fingerprints and light oils without the use of solvent cleaners.

2363-50 50 - 8"x 8" (20cm x 20cm) dry wipes w/hemmed edges, double-bagged



- Cleans & polishes glass or plastic
- Low-linting
- Washable (avoid fabric softener)

LCD & Plasma Screen Cleaning Wipes

Soft and low-linting microfiber terry cloth is ideal for cleaning and polishing LCD and plasma screens, plexi-glass, chrome, and other sensitive surfaces. Buffs surface to a shine with or without cleaner.

2368-2 2 - 16"x 16" (40.6cm x 40.6cm) dry wipes w/hemmed edges



- Cleans & polishes sensitive surfaces
- Perfect for chrome polishing
- Effective wet or dry
- Washable (avoid fabric softener)
- Low-linting

Roll Wipes for DEK and MPM SMT Printers

Made from low lint fabric and designed for vacuum operation.

- Maximum absorency
- Strong both wet & dry
- Textured non-woven poly-cellulose fabric
- Low linting – prevents misprints
- Density 68 GSM



Part #	OEM Brand	Equip model	Core ID	Notch	Paper Width	Core Width	Matl Length
2366-DEK	DEK	DEK 265, #129051/GS, GSX & 288	0.75" (19mm)	1	20.3" (515mm)	20.9" (530mm)	39' (11.9 M)
2367-MPM	MPM	MPM #1485/AP & UP2000	0.75" (19mm)	0	17.5" (444mm)	18" (457mm)	39' (11.9 M)



TechSwabs

Precisely designed, manufactured and packaged to serve a wide variety of cleaning and maintenance needs. TechSwabs are manufactured in accordance with Techspray's rigid specifications, using specialized materials to ensure low particle generation.

Cotton TechSwabs

Tightly wrapped, pre-cleaned cotton ensures the least amount of extractable contaminants. The most economical choice for high volume usage.

All swabs shown actual size – 1:1 scale

Product	Tip Width	Attachment of Tip	Handle Length	Handle Material	50 Pack Bag	100 Pack Bag	1000 Pack Bag
2300	0.1875" (4.8mm)	Wrapped	6" (15cm)	Wood	—	2300-100	2300-1000
2301	0.1875" (4.8mm)	Wrapped	6" (15cm)	Wood	—	2301-100	2301-1000
2313	0.125" (3.2mm)	Wrapped	3.25" (8.3cm)	Paper	2313-50PK	—	—

Foam TechSwabs

All foam swabs are manufactured with 100 pores per inch reticulated polyurethane foam, which ensures excellent absorbency while minimizing contamination. Tips are affixed by heat seal to prevent tip loss, even while saturated with solvent. Flexible tips provide versatility and softer touch, while rigid heads allow for more aggressive cleaning.

Product	Tip Width	Attachment of Tip	Handle Length	Handle Material	50 Pack Bag	1000 Pack Bag
2302	0.44" (11.2mm)	Heat Sealed	6" (15cm)	Polypropylene	2302-50	2302-1000
	<i>Cotton Bud Wrapped in Foam, Rigid Head</i>					
2303	0.19" (4.8mm)	Heat Sealed	6" (15cm)	Polypropylene	2303-50	2303-1000
	<i>Rigid Head</i>					
2306	0.5" (13mm)	Heat Sealed	5" (13cm)	Polypropylene	2306-50	2306-1000
	<i>Rigid Head</i>					
2307	0.19" (4.8mm)	Heat Sealed	4" (10cm)	Polypropylene	2307-50	2307-1000
	<i>Flexible Tip</i>					
2309	0.125" (3.2mm)	Heat Sealed	3" (7.6cm)	Polypropylene	—	2309-1000
	<i>Flexible Tip</i>					
2311	0.125" (3.2mm)	Heat Sealed	2.625" (6.7cm)	Polypropylene	—	2311-1000
	<i>Flexible Tip</i>					



TECHSPRAY®



Fiber Optic TechSwabs CLASS 100

All swabs shown actual size – 1:1 scale

Product	Tip Width	Attachment of Tip	Handle Length	Handle Material	50 Pack Bag	1000 Pack Bag
2316	0.05" (1.25mm)	Heat Sealed	6.25" (16cm)	Polypropylene	2316-50	2316-1000
	<i>Flexible Tip</i>					
2317	0.1" (2.5mm)	Heat Sealed	6.25" (16cm)	Polypropylene	2317-50	2317-1000
	<i>Flexible Tip</i>					


Brushes

Techspray's TechClean® brushes are made of premium grade materials. Don't be fooled by cheap imports. Bristles are securely stapled in place, eliminating loose bristles.

Choose the Right Bristle Material for Your Needs:

Natural — Soft, resilient and long lasting. Hog bristles are stiffer than horsehair.

Metal — For burnishing, polishing, non-sparking static dissipation and deburring. Brass is a softer bristle than stainless steel.



Selecting the right brush:

Brushes dimensions are specified as bristle length (L), width (W), and trim (T).

General Cleaning Brushes

A wide variety of sizes and bristle material for general maintenance cleaning. All handles are made of strong, static neutral wood.

FRONT VIEW	SIDE VIEW	Product	L Bristle Length	W Bristle Width	T Bristle Trim	Bristle Material	Handle Material	Handle Length
		2020-1	1.375" (35mm)	0.25" (6.4mm)	0.44" (11mm)	Horse Hair	Wood	7.75" (19.7cm)
		2021-1	1.375" (35mm)	0.25" (6.4mm)	0.44" (11mm)	Hog Bristle	Wood	7.75" (19.7cm)
		2022	2.125" (54mm)	0.875" (22mm)	0.75" (19mm)	Hog Bristle	Wood	8.375" (21.3cm)
		2025-1	1.375" (35mm)	0.25" (6.4mm)	0.44" (11mm)	Brass .003" (0.08mm)	Wood	7.75" (19.7cm)
		2027-1	0.875" (22mm)	0.375" (9.5mm)	0.5" (12.7mm)	Hog Bristle	Wood	4.94" (12.5cm)



Static Sensitive Brushes

Ideal for cleaning static sensitive electronics or components. Anodized aluminum falls within the static dissipative range (10^5 to 10^{12} ohms/square per ASTM D-257). Steel bristles are conductive, and horse hair is dissipative when saturated with solvent.

FRONT VIEW	SIDE VIEW	Product	L Bristle Length	W Bristle Width	T Bristle Trim	Bristle Material	Handle Material	Handle Length
		2040-1	1.19" (30.2mm)	0.125" (3.2mm)	0.44" (11.2mm)	Horse Hair	Anodized Aluminum	6.44" (16.4cm)
		2042-1	1.19" (30.2mm)	0.375" (9.5mm)	0.44" (11.2mm)	Horse Hair	Anodized Aluminum	6.44" (16.4cm)
		2043-1	1.19" (30.2mm)	0.375" (9.5mm)	0.44" (11.2mm)	Stainless Steel .003" (0.08mm)	Anodized Aluminum	6.44" (16.4cm)

Technical Brushes

Small, precision brushes for technical cleaning and coating or adhesive application. Double-sided brushes include tapered end for tight areas.

FRONT VIEW	SIDE VIEW	Product	L Bristle Length	W Bristle Width	T Bristle Trim	Bristle Material	Handle Material	Handle Length
		2030-1	0.125" (3.2mm)	0.0625" (1.6mm)	0.125" (3.2mm)	Goat Hair	Stainless Steel	3.5" (8.9cm)
	 <i>Top View</i> <small>TECHSPRAY #2031</small>	2031-1	0.25" (6.4mm)	0.19" (4.8mm)	A - 0.25" (6.4mm) B - 0.5" (13mm)	Horse Hair	Stainless Steel	4.5" (11.4cm)
	 <i>A Side View B</i>	2032-1	0.5" (13mm)	0.375" (9.5mm)	A - 0.19" (4.8mm) B - 0.25" (6.4mm)	Horse Hair	Zinc Plated Steel	4.5" (11.4cm)
	 <small>TECHSPRAY #2033</small>	2033-1	0.44" (11.2mm)	0.375" (9.5mm)	0.75" (19mm)	Horse Hair	Zinc Plated Steel	4.5" (11.4cm)



Index — Industry Approvals

Call Out	Part#	Page
AT&T Com Code #406359406	1702-G	16
AT&T Com Code #406359414	1733-QT	16
Boeing Aircraft (127713)	1632	6
Boeing Aircraft (BAC5485)	1720	16
Celestica 8500-4214	2206	20
Celestica 8690-0576	1821	23
Celestica 8690-0577	1823	23
Celestica 8690-0588	1822	23
Celestica 8710-2129	2025-1	29
Celestica 9300-0468	2302-1000	28
Celestica 9300-0468	2303-1000	28
Celestica 9300-1618	2350-100	26
Celestica 9300-1731	1702-8FP	16
Celestica 9300-1921	1733-G	16
Celestica 9300-6148	1702-G	16
Chrysler Corp. NPM	1671	2
#85-147-6381		
Delco C00012555	1671-155	2
Delco C00013781	1726	16
Delco C00038201	1702	16
Delco C00054786	1747	22
FORD TOX #039772	2211	21
FORD TOX #142415	1612-25Q	9
FORD TOX #142422	1613-25Q	9
FORD TOX #142430	1620 (aerosol)	8
FORD TOX #142431	1621 (aerosol)	12
FORD TOX #142435	1671-10S	2
FORD TOX #142434	1672	22
FORD TOX #167818	1630-16S	6
FORD TOX #167834	1631-16S	11
FORD TOX #167835	1632-16S	6
General Dynamics	1720	16

Call Out	Part#	Page
GM Cadillac-Flint H1013	1621 (aerosol)	12
GM Cadillac-Flint H1015	1620 (aerosol)	8
GM Cadillac-Flint H1017	1622 (aerosol)	8
GM Powertrain Flint HMA	1671	2
120993-F		
GM Powertrain Flint HMA	1672	22
120993-H		
Hewlett Packard 8500-4214	2206	20
Hewlett Packard 8500-6344	1747-10S	22
Hewlett Packard 8690-0576	1821	23
Hewlett Packard 8690-0577	1823	23
Hewlett Packard 8690-0588	1822	23
Hewlett Packard 8710-2129	2025-1	29
Hewlett Packard 9300-0468	2302-1000	28
Hewlett Packard 9300-0468	2303-1000	28
Hewlett Packard 9300-1618	2350-100	26
Hewlett Packard 9300-1731	1702-8FP	16
Hewlett Packard 9300-1921	1733-G	16
Hewlett Packard 9300-6148	1702-G	16
McDonnell Douglas	1672	22
558-1672-10S		
Motorola Service Centers	2211-G	21
NCR 603-8001308	1747	22
NSN 6830-01-335-9925	1671-10S	2
NSN 6850-01-324-4682	1726	16
NSN 6850-01-406-1356	1672	22
Unisys	1720	16
USDA Accepted K2	1620 (aerosol)	8
USDA Accepted K2	1621 (aerosol)	12
USDA Accepted K2	1621 (bulk)	8,12
USDA Accepted K2	1622 (aerosol)	8

Index — Standards & Specifications

Specs	Part#	Page
ACS Reagent Grade IPA	1610	3
ASTM D770-05	1610	3
Fed Spec TT-1-735A	1610	3
IPC-CC-830B	2102	17
IPC-CC-830B	2104	19
IPC-CC-830B	2108, 2109, 2151	19
MIL-B-81705B	1726	16
MIL-B-81705B	1743	16
MIL-F-142560D Type R	1801-1813	23
MIL-I-46058C Type SR	2102	17
MIL-I-46058C Type SR	2106	17
MIL-I-46058C Type UR	2104	19
MIL-I-46058C Type AR	2108, 2109, 2151	19

Call Out	Part#	Page
MIL-STD-2000 Para 5.3.18	2205, 2211	21, 22
parts a, b, & d		
NASA NHB 5300.4(3A-1)	1801-1813	23
NASA NPC 200-4	1801-1813	23
NASA SP5002	1801-1813	23
NFPA 56A	1720	16
NFPA 56A	1726	16
NFPA 56A	1743	16
UL94 V-0, file #E95150	2102	17
UL94 V-0	2104, 2108, 2109	19
USAF requirements	2350	26
(for surface contamination)		



Go to www.techspray.com

for up-to-date product specs, documents,
videos & more!



Index by Part Number

Part#	Page #	Part#	Page #	Part#	Page #	Part#	Page #	Part#	Page #	Part#	Page #	Part#	Page #
1505-G.....	9	1610-54G	3	1656-5G.....	13	1808-5F.....	23	1978-DP	24	2205-G.....	20	2363-50.....	27
1505-QT.....	9	1610-5G.....	3	1656-G.....	13	1809-10F	23	2020-1	29	2206-G.....	20	2364-50.....	26
1520-54G	14	1610-G1.....	3	1671-10S.....	2	1809-25F	23	2021-1	29	2211-54G	21	2365-300.....	26
1520-5G.....	14	1610-G4.....	3	1671-15S.....	2	1809-5F	23	2022-1	29	2211-5G.....	21	2366-DEK	27
1520-G.....	14	1610-P.....	3	1672-10S.....	22	1810-100F	23	2025-1	29	2211-8SQ	21	2367-MPM	27
1520-2SQ	9	1610-PT.....	3	1672-15S.....	22	1810-10F	23	2027-1	29	2211-G.....	21	2368-2	27
1520-G.....	14	1612-2SQ	9	1673-10S.....	2	1810-25F	23	2030-1	30	2222-8SQ	21	2505-N.....	24
1520-6S.....	9	1613-6S.....	9	1680-54G	13	1810-5F	23	2031-1	30	2222-G.....	21	2506-N.....	24
1530-54G	14	1620-10S.....	8	1680-5G.....	13	1811-100F	23	2032-1	30	2300-100.....	28	2507-N100	24
1530-5G.....	14	1621-10S.....	12	1680-G.....	13	1811-10F	23	2033-1	30	2300-1000	28	2507-N.....	24
1530-G.....	14	1621-10SB	12	1681-54G	13	1811-25F	23	2040-1	30	2301-100.....	28	2509-GN	24
1550-54G	14	1621-54G	8,12	1681-5G.....	13	1811-5F	23	2042-1	30	2301-1000	28	2510-N.....	19,24
1550-5G.....	14	1621-5G.....	8,12	1681-G.....	13	1812-5F	23	2043-1	30	2302-1000	28	2510-P.....	19,24
1550-G.....	14	1621-G.....	8,12	1686-54G	13	1813-5F	23	2102-12S.....	17	2302-50.....	28	2851-20S.....	7
1555-P.....	14	1622-10S.....	8	1686-5G.....	13	1820-10F	23	2102-5G.....	17	2303-1000	28	3400-20S.....	5,13
1570-100DSP	15	1622-13S.....	8	1686-G.....	13	1820-50F	23	2102-G.....	17	2303-50.....	28	3400-54G	5,13
1570-G.....	15	1625-18S.....	9	1697-10S.....	2	1820-5F	23	2102-GHV.....	17	2306-1000	28	3400-5G	5,13
1570-QT.....	15	1630-16S.....	6	1697-8S.....	2	1821-10F	23	2102-P.....	17	2306-50.....	28	3400-G	5,13
1571-15RTU-5G ..	15	1631-16S.....	11	1702-8FP.....	17	1821-25F	23	2104-12S.....	19	2307-1000	28	3401-54G	11,13
1571-54G	15	1631-16SB	11	1702-G.....	17	1821-50F	23	2104-5G.....	19	2307-50.....	28	3401-5G	11,13
1571-5G.....	15	1631-5S.....	11	1720-5G.....	17	1821-5F	23	2104-G.....	19	2309-1000	28	3401-G	11,13
1571-G.....	15	1632-16S.....	6	1720-G.....	17	1822-100F	23	2105-G.....	19	2311-1000	28	3500-11S	9
1572-54G	15	1634-12S.....	11	1726-QT.....	17	1822-10F	23	2106-12S.....	17	2313-50.....	28	3505-11S	9
1572-5G.....	15	1635-20S.....	6	1733-G.....	17	1822-50F	23	2106-G.....	17	2316-1000	29	3510-12S	9
1572-G.....	15	1638-54G	6,11	1733-QT.....	17	1822-5F	23	2108-12S.....	19	2316-50.....	29	53-4001-0533 ..	21
1573-5G.....	15	1638-5G.....	6,11	1743-50PK	17	1823-100F	23	2108-5G.....	19	2317-1000	29	53-4003-0533 ..	21
1573-G.....	15	1638-G.....	6,11	1743-QT.....	17	1823-10F	23	2108-G.....	19	2317-50.....	29	53-4004-0533 ..	21
1573-QT.....	15	1647-16S.....	7	1747-10S.....	22	1823-25F	23	2108-P.....	19	2340-100.....	26	CAN1671-10S ..	2
1583-10S.....	23	1651-16S.....	6,12	1756-5G.....	17	1823-5F	23	2109-5G.....	19	2342-300.....	26	CAN1671-15S ..	2
1608-100DSP	3	1651-54G	6,12	1756-8S.....	17	1824-25F	23	2109-G.....	19	2350-100.....	26	CAN1672-10S ..	22
1608-100FL	3	1651-5G.....	6,12	1756-54G	17	1824-5F	23	2109-P.....	19	2351-100.....	26		
1608-100R	3	1654-54G	13	1756-G.....	17	1825-5F	23	2110-P.....	19	2352-100.....	26		
1608-G4.....	3	1654-5G.....	13	1802-100F	23	1830-10F	23	2120-5G.....	18	2355-100.....	26		
1610-100DSP	3	1654-G.....	13	1802-500F	23	1831-10F	23	2120-P.....	18	2357-100.....	27		
1610-100FL	3	1655-54G	13	1803-500F	23	1832-5F	23	2120-G.....	18	2358-50.....	27		
1610-100R	3	1655-5G.....	13	1804-500F	23	1833-10F	23	2204-8SQ	20	2359-300.....	26		
1610-12S.....	3,8	1655-G.....	13	1808-100F	23	1977-DP	24	2204-G.....	20	2362-4x4-200 ..	27		
1610-50PK	3	1656-54G	13	1808-10F	23	1978-1.....	24	2205-8SQ	20	2362-150.....	27		

Techspray - US Office
 8125 Cobb Center Drive
 Kennesaw, GA 30152
 678-819-1408
 800-858-4043
 tsales@techspray.com

Techspray - European Office
 ITW Contamination Control BV
 Saffierlaan 5, 2132 VZ Hoofddorp
 The Netherlands
 +31 88 1307 400
 info@itw-cc.com

Techspray - China Office
 ITW Specialty Materials (Suzhou) Co., Ltd
 Hengqiao Road, Wujiang Economic
 Development Zone,
 Suzhou, Jiangsu Province, China 215200
 (86)512-82060808 Ext 508
 MP: (86) 13777018750